

08/02/2006 08:57

3238876559

CALFLEX MFG

PAGE 02



# HOFFMAN PLASTIC COMPOUNDS INC.

16616 GARFIELD AVENUE, PARAMOUNT, CALIFORNIA 90723-5305

TEL: (323) 636-3346 - FAX: (562) 630-8200

www.hoffmanplastic.com

e-mail: info@hoffmanplastic.com

## MATERIAL SAFETY DATA SHEET

MSDS DATE: June 26, 2006

PRODUCT NAME: V4-22 LOW TINT CLEAR

### I. PRODUCT IDENTIFICATION

#### HMIS HAZARD RATING

HEALTH HAZARD: 0      FIRE HAZARD: 1      REACTIVITY: 0      PPE: A

Based on the National Paint & Coatings Association HMIS rating system.

#### SARA / TITLE III HAZARD CATEGORIES

Immediate (ACUTE) Health: NO      Reactive Hazard: NO  
 Delayed (CHRONIC) Health: NO      Sudden release of pressure: NO  
 Fire Hazard: NO

MANUFACTURERS      HOFFMAN PLASTIC COMPOUNDS, INC.  
 NAME &      16616 GARFIELD AVE.  
 ADDRESS      PARAMOUNT, CA 90723

EMERGENCY PHONE: (323) 636-3346      CHEMTREC: (800) 424-9300

CHEMICAL NAME: Not applicable -- Mixture of materials

SYNONYMS / COMMON NAMES: Polyvinyl Chloride (PVC) Vinyl Compounds

DOT PROPER SHIPPING NAME: N/A  
 DOT HAZARD CLASS: N/A  
 DOT I.D. NUMBER: N/A  
 DOT HAZARDOUS SUBSTANCE: N/A

### II. HAZARDOUS INGREDIENTS

#### RESIDUAL VINYL CHLORIDE MONOMER

Note: Vinyl Chloride (VCM) is an OSHA regulated material (refer to OSHA 1910.1017 for details)

Material heated at 350 degrees as less than .01 part VCM / m3.

HOFFMAN PLASTIC COMPOUNDS, INC. certifies that all ingredients &/or materials used in the manufacture of our vinyl (plastic) compounds have been registered in accordance to the rules of the Toxic Substances Control Act.



**VI. REACTIVITY DATA**

STABILITY: Stable

CONDITIONS TO AVOID: Excessive heat for prolonged periods

MATERIALS TO AVOID: Acetal &/or Acetal Copolymers or with Amine containing Materials during processing

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2, HCL

HAZARDOUS POLYMERIZATION: Will not occur

**VII. SPECIAL PROTECTION**

VENTILATION REQUIREMENTS: General room ventilation

**SPECIFIC PERSONAL PROTECTIVE EQUIPMENT**

RESPIRATORY: A NIOSH/MSHA approved respirator should be worn if the PEL is exceeded

EYE: Wear safety glasses with side shields (ANSI Z87.1, 1979)

GLOVE: Not necessary, but sensitive people should wear them.

**VIII. HANDLING & STORAGE**

HANDLING & STORAGE PRECAUTIONS:  
Store in closed containers in a cool, dry, well ventilated area, away from direct heat

**IX. ENVIRONMENTAL PROCEDURES**

SPILL &/OR LEAK PROCEDURES:  
Carefully sweep or vacuum up and place in marked containers for reuse or recycle

WASTE DISPOSAL METHOD:  
Dispose in accordance with federal, state, & local government regulations.

---

**X. ADDITIONAL INFORMATION**

---

OSHA standard 29CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, material safety data sheets, training and access to written records. We request that you & it is your legal obligation to make all information in this Material Safety Data Sheet available to your employees.

To aid our customers in complying with regulatory requirements, SARA Title III hazard categories for this product are indicated in section 1. If the word "YES" appears next to any category, this product may be reported by you under the requirements of 40CFR Part 370. Please consult those regulations for details.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

PREPARED/REVISED BY: Roland Hoffman  
December, 2001

The data and recommendations presented herein are based upon a review of HOFFMAN PLASTIC COMPOUNDS, INC. files, published MSDS's, and standard toxicological reference sources. HOFFMAN PLASTIC COMPOUNDS, INC. makes no guarantee or warranty, either expressed or implied as to the accuracy or completeness of these data and recommendations.